

CUJ 系列自由安装气缸


Free mounting cylinder



图形符号 symbols



双作用
Double acting



单作用 (弹簧压回)
Spring Acting(spring back)

型号注释 Order Code

CUJ (B) (4) - (6) (S) () 基本型/basic
 CDUJ (B) (8) - (10) (D) (M) - (M9N) (S) 内置磁环型/With magnetic ring

- 通孔安装 through hole mounting
- 缸径/bore 4:φ4mm 6:φ6mm 8:φ8mm 10:φ10mm
*φ4mm气缸没有内置磁环型
- 行程/Stroke
- 动作方式/Acting type
D:双作用/Double acting S:单作用 (弹簧压回) /Single acting(spring back pressure)
- 活塞杆形式 :Threads type
无记号-杆端内螺纹 (φ4mm没有螺纹) Null: femal thread(No thread for φ4)
M-杆端外螺纹 M:male thread
- 磁性开关的型号/Magnetic switch model 无记号/blank:无磁性开关/no
磁性开关型号参见行程/磁性开关型号表
- 磁性开关个数 无记号:2个 S: 1个 /Magnet switch qty: Null:2pc S:1pc

行程/磁性开关型号表 /Magnet switch code

缸径/bore mm	标准行程 (mm) Standard Stroke		轨道安装/Track/Magnetic switch code *磁性开关型号
	双作用/double acting	单作用/single acting	
4	4,6,8,10,15,20	4,6	M9N
6	4,6,8,10,15,20,25,30	4,6,8	M9B
8	4,6,8,10,15,20,25,30	4,6,8,10	M9P
10			

*磁性开关规格特性可参阅磁性开关的系列, 在磁性开关型号后面, 附导线长度表示记号, 无记号为0.5m, L为3m, Z为5m

Magnetic switch specifications and characteristics can refer to the magnetic switch series. The wire length with mark, no sign -0.5m, L-3m, z-5m, for example: Z73, Z73L.

技术参数 Specification

缸径 (mm)	4	6	8	10
使用流体 /working medium Type	空气/air			
动作方式 /Acting type	双作用/单作用(弹簧压回) / double acting/Single acting: spring back			
最高使用压力 /Max. operating pressure	0.7MPa			
最低使用压力 /Min operating pressure	双作用 /double acting 单作用 /single acting	0.15	0.3	0.1 0.2
环境和流体温度 /Environment and fluid temperature	带磁性开关/With magnetic switch : -10-60°C, 无磁性开关/non magnetic switch : -10-70°C			
缓冲 /Cushion	无/no			
使用活塞速度/piston speed	50-500mm/s			
行程公差/Stroke tolerance range (mm)	±0.05			
*给油/ Lubricate	不需要/no			
安装形式/Mounting opinion	通孔、自由 (多面) 安装/Through hole, free (multi-faceted) mounting			
接管口径 / Threads	M3×0.5			