


CXS 系列双缸气缸

Series twin-rods cylinder



图形符号 symbols



产品特点 Features

1. 薄且轻性: 在保持既有动作精度及产品使用寿命下, 其全长仅为一般气缸的1/2-1/3。发挥既薄且轻的特性;
2. 易安装性: 使用埋入式的安装方式, 不需要任何配件达到节省空间的要求;
3. 易维修性: 采用简易的组装方式进行设计, 方便装拆及维修;
4. 磁控简单性: 在主体四周预留装配槽, 使磁性开关在安装固定及位置调整时, 均极具简单;

1. Thin and light: to maintain the existing action accuracy and product life, the full length of only the general cylinder 1 / 2-1 / 3. Play both thin and light;
2. Easy to install: the use of embedded installation, do not need any accessories to save space requirements;
3. Easy to maintain: the use of simple assembly design, easy assembly and repair and maintenance;

技术参数 Specification

缸径/bore (mm)	6	10	15	20	25	32
流体/ Fluid	空气/ Air					
动作方式/ Motion pattern	双作用/ Double Action					
最高使用压力/ Max operating pressure(MPa)	0.7					
最低使用压力/Min operating pressure (MPa)	0.15	0.1	0.05			
环境和流体温度 Environment and fluid temperture	-10~+60°C					
缓冲/ Cushion	两端橡胶缓冲/damper(Both side)					
使用活塞速度mm/s piston speed	30-300	30-800	30-700		30-600	
结构/ Structure	双气缸 (2倍输出力) / twin rods (double force)					
*润滑/ Lubricate	不需要/ No					
行程调整范围 / Stroke adjustment range (mm)	缩回行程0~-5mm/Retract stroke 0 ~ -5mm					
轴承/ bearing	滑动轴承/球轴承/slide/Ball bearing					
活塞杆不回转精度 /no rational	滑动轴承/Slide bearing	±0.1°				
	球轴承/Ball bush bearing	±0.1°				
接管口径Rc/Threads	M5X0.8					1/8

*如需润滑, 请用透平1号油 ISOVG32 / Pls use ISOV32 1 for lubricate , if necessary

型号注释 Order Code

C X S M 20 - 100 - Z73

轴承种类/Bearing
M: 滑动轴承/ slide L :球轴承/Ball bearing

缸径/bore

行程/Stroke

磁性开关型号 /magnet sensor

无记号/no mark 无磁性开关/ no magnet sensor

磁性开关型号 /order stroke / magnet switch

参见行程/磁性开关型号表 /See stroke/magnetic switch model table

磁性开关个数

无记号 2个 no mark 2 pcs

S 1个 S 1 pcs

N N个 N N pcs

行程/磁性开关型号 order stroke / magnet switch

缸径 /bore (mm)	标准行程/standard	磁性开关型号 magnet sensor (轨道安装) guider type
		Z73
6	10, 20,30,40,50,	Z73
10	10,20,30,40,50,60,70,75	
15		
20	10,20,30,40,50,60,70,75,80,90,100	
25		
32		

磁性开关规格及特性可参阅磁性开关系列。导线长度表示记号: 无记号-0.5m, L-3m, z-5m
例: Z73, Z73L

Magnetic switch specifications and characteristics can refer to the magnetic switch series. The wire length with mark, no sign -0.5m, L-3m, z-5m, for example: Z73, Z73L.